

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 06/09/2023 Revision date: 06/09/2026 Supersedes version of: 03/08/2020 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Completely Denatured Alcohol (CDA) Dyed

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Manufacture of substances

Intermediates

Distribution of substance

Formulation (re)packing of substances and mixtures

Uses in Coatings

Cleaning/washing agents and additives

Fuels

Function or use category Laboratory chemicals Anti-freezing agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Leading Solvent Supplies Ltd
Marston Business Park Rudgate
Tockwith York – North Yorkshire
United Kingdon

T +44 (0) 1423 358058 - F +44 (0)1423 358923

enquiries@leading-solvents.co.uk

Supplier information

Leading Solvents Ireland Ltd The Courtyard Manor House 3 Church Road

Malahide – Co.Dubin

Ireland

T +353 1 845 7660

1.4. Emergency telephone number

Emergency number : +44 (0) 1423 358058 (Office hours only)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 Serious eye damage/eye irritation, Category 2 H319

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger Contains : Ethanol

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H319 - Causes serious eye irritation.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+P378 - In case of fire: Use foam, carbon dioxide (CO2), dry extinguishing powder to

extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

 $\ensuremath{\mathsf{P501}}$ - Dispose of contents and container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610- 43	≥ 90	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Propan-2-ol substance with national workplace exposure limit(s) (DE, GB, NL)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119451558- 25	≥1-<5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Methyl Ethyl Ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	≥ 1 – < 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Keep affected person under observation. Effects may be delayed. If in doubt, get medical

attention promptly. Show this Safety Data Sheet to the medical personnel.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing. If breathing is irregular or stopped, administer artificial respiration. If

experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin

irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Get immediate medical advice/attention. Rinse mouth out with water. Do NOT induce

vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the

lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : Causes skin irritation. irritation (itching, redness, blistering). Repeated exposure may cause

skin dryness or cracking.

Symptoms/effects after eye contact : redness, itching, tears. Causes eye irritation. stinging.

Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting. May be harmful if swallowed. May cause

irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable liquid and vapour. Heating may cause a fire or explosion.

Explosion hazard : The vapour may be invisible, heavier than air and spread along ground. Vapours may form

explosive mixture with air.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent from entering sewers, basements and workpits, or any place where its

accumulation can be dangerous. Stop leak if safe to do so.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes.

06/09/2026 (Revision date) EN (English) 3/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite.

Methods for cleaning up : Take up liquid spill into absorbent material. Absorb remaining liquid with sand or inert

absorbent and remove to safe place. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Storage area : Store away from heat.

Special rules on packaging : Keep only in original container.

Packaging materials : Keep only in the original container in a cool,well-ventilated place away from combustible

materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Ethanol (64-17-5)		
United Kingdom - Occupational Exposure Limits		
Local name Ethanol		
WEL TWA (OEL TWA) [1]	1920 mg/m³	
WEL TWA (OEL TWA) [2]	1000 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propan-2-ol (67-63-0)		
United Kingdom - Occupational Exposure Limits		
Local name	Propan-2-ol	
WEL TWA (OEL TWA) [1]	999 mg/m³	
WEL TWA (OEL TWA) [2]	400 ppm	
WEL STEL (OEL STEL)	1250 mg/m³	
WEL STEL (OEL STEL) [ppm]	500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Methyl Ethyl Ketone (78-93-3)		
United Kingdom - Occupational Exposure Limits		
Local name	Butan-2-one (methyl ethyl ketone)	
WEL TWA (OEL TWA) [1]	600 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	899 mg/m³	
WEL STEL (OEL STEL) [ppm]	300 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Butan-2-one (methyl ethyl ketone)	
BMGV	70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):











8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type Field of application Characteristics Standard			
Safety glasses, Safety goggles	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC)	5 (> 240 minutes)	0.44		EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device Filter type Condition Standard			Standard
Aerosol mask	ABEK	Vapour protection, Protection for Liquid particles	EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

06/09/2026 (Revision date) EN (English) 6/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colour : Purple. Odour : alcoholic. Odour threshold : Not available Melting point -114 °C Freezing point Not available Boiling point 78 °C @ 1013 hPa Flammability : Not applicable Lower explosion limit : 2.5 vol % Upper explosion limit : 13.5 vol % Flash point : 12 °C Closed cup.

Auto-ignition temperature : 363

Decomposition temperature : Not available : Not available рΗ Not available Viscosity, kinematic · 12 mPa.s Viscosity, dynamic Solubility : Soluble in water. Partition coefficient n-octanol/water (Log Kow) : Not available Partition coefficient n-octanol/water (Log Pow) : 0.35 Vapour pressure : 5.8 kPa Vapour pressure at 50°C : Not available Density : 0.79 - 0.82 kg/l Relative density : Not available

Relative vapour density at 20°C : 1.03

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : 3.4 VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acute toxicity (dermal) : Not classified	
Acute toxicity (inhalation) : Not classified	
Ethanol (64-17-5)	
LD50 oral rat 10470 mg/kg bw/day	
LD50 oral 8300 mg/kg bodyweigh	Animal: mouse, Remarks on results: other:
LD50 dermal rat 15800 mg/kg	
LC50 Inhalation - Rat (Vapours) 20 mg/l/4h	
Propan-2-ol (67-63-0)	
LD50 oral 5840 mg/kg	
LD50 dermal 13900 mg/kg	
LC50 Inhalation - Rat (Dust/Mist) 25000 mg/l/4h	
Methyl Ethyl Ketone (78-93-3)	
LD50 oral rat > 2193 mg/kg	
LD50 dermal rabbit > 5000 mg/kg (OECD T	est Guideline 402)
LC50 Inhalation - Rat 34 mg/l (Rat; 4 h)	
Skin corrosion/irritation : Not classified	
Ethanol (64-17-5)	
pH 7	
Propan-2-ol (67-63-0)	
pH 5.5	
Methyl Ethyl Ketone (78-93-3)	
pH 7	
Serious eye damage/irritation : Causes serious eye irrita	tion.
Ethanol (64-17-5)	
pH 7	
Propan-2-ol (67-63-0)	
pH 5.5	
Methyl Ethyl Ketone (78-93-3)	
pH 7	
Respiratory or skin sensitisation : Not classified	
Germ cell mutagenicity : Not classified	
Carcinogenicity : Not classified	
Reproductive toxicity : Not classified STOT-single exposure : Not classified	
Propan-2-ol (67-63-0)	
STOT-single exposure May cause drowsiness	or dizziness.
Methyl Ethyl Ketone (78-93-3)	
STOT-single exposure May cause drowsiness	or dizziness.
STOT-repeated exposure : Not classified	

06/09/2026 (Revision date) EN (English) 8/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethanol (64-17-5)		
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)	
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)	
Methyl Ethyl Ketone (78-93-3)		
NOAEC (inhalation, rat, gas, 90 days)	5041 ppmv/6h/day 4 month; 6 hours/day) (OECD Test Guideline 413); No adverse effect has been observed with repeated intake in toxicity tests.	
Aspiration hazard :	Not classified	
Propan-2-ol (67-63-0)		
Viscosity, kinematic	3.115 mm ² /s	
Methyl Ethyl Ketone (78-93-3)		
Viscosity, kinematic	0.519 mm²/s	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

: Not classified

: Not classified

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

Not rapidly degradable

vot rapidity degradable		
Ethanol (64-17-5)		
LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas	
LC50 - Fish [2]	> 100 mg/l Leuciscus idus (Golden orfe)	
EC50 72h - Algae [1]	275 mg/l (Chlorella vulgaris)	
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'	
NOEC chronic fish	9.6 mg/l Daphnia magna	
Propan-2-ol (67-63-0)		
LC50 - Fish [1]	9640 mg/l	
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea	
EC50 - Other aquatic organisms [2]	> 1000 mg/l	

06/09/2026 (Revision date) EN (English) 9/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl Ethyl Ketone (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Completely Denatured Alcohol (CDA) Dyed		
Partition coefficient n-octanol/water (Log Pow)	0.35	
Ethanol (64-17-5)		
Partition coefficient n-octanol/water (Log Pow) 0.31		
Propan-2-ol (67-63-0)		
Partition coefficient n-octanol/water (Log Pow) 0.05		
Methyl Ethyl Ketone (78-93-3)		
Partition coefficient n-octanol/water (Log Kow)	0.3 (40 °C)	

12.4. Mobility in soil

Methyl Ethyl Ketone (78-93-3)	
Surface tension	24.8 mN/m (20 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Additional information

- $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$
- : Flammable vapours may accumulate in the container.

06/09/2026 (Revision date) EN (English) 10/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	number			
UN 1170	UN 1170	UN 1170	UN 1170	UN 1170
14.2. UN proper shippin	g name			
ETHANOL (ETHYL ALCOHOL) / ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL (ETHYL ALCOHOL)	Ethanol solution	ETHANOL (ETHYL ALCOHOL)	ETHANOL (ETHYL ALCOHOL)
Transport document descr	ription			
UN 1170 ETHANOL (ETHYL ALCOHOL) / ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II, (D/E)	UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II	UN 1170 Ethanol solution, 3, II	UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II	UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II
14.3. Transport hazard	class(es)			
3	3	3	3	3
3	3	3	3	3
14.4. Packing group	,			
II	II	II	II	II
14.5. Environmental haz	zards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	on available	ı	ı	ı

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 144, 601
Limited quantities (ADR) : 11

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates :

33 1170

Tunnel restriction code (ADR) : D/E EAC code : •2YE

Transport by sea

Special provisions (IMDG) : 144 Limited quantities (IMDG) 1 L Excepted quantities (IMDG) E2 Packing instructions (IMDG) P001 IBC packing instructions (IMDG) IBC02 Tank instructions (IMDG) T4 Tank special provisions (IMDG) TP1 : F-E EmS-No. (Fire) : S-D EmS-No. (Spillage) Stowage category (IMDG) : A

Properties and observations (IMDG) : Colourless, volatile liquids.Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to

19% Miscible with water.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A58, A180

ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 144, 601
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 144, 601
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2

Packing instructions (RID) : P001, IBC02, R001

Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portable tank and bulk container special provisions : TP

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 100 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
1.3	Display additional SDS EU addresses	Added	
1.4	Additional information	Added	NHS 111 & EU Poison Centre

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.