



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

Guide#7

Dry Guide Coat

DESCRIPTION

A highly effective dry powder guide coat that highlights and identifies surface imperfections when sanding filler or primers

- Does not clog or block abrasives
- Suitable for dry or wet sanding
- Dries instantly

TECHNICAL DATA



Mixing

Shake the aerosol can for at least 2 minutes before use.

Spray directly onto the cured bodyfiller or primer, GUIDE#7 dries in seconds, sand to required finish any low spots will show as black.

STORAGE & VOC INFORMATION



Shelf Life

2 years subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 5°C - 25°C

Recommended Application Temperature 20°C



VOC Information

The EU limit for this product (product category: IIB.e) in ready to use form is 840g/litre. The VOC content of this product in ready to use form is 680 g/litre.

Order Code	Format	Colour	VOC g/l
GUIDE/AL	450ml Aerosol	Black	680

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyer's responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and therefore U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL Ltd
The Grange, 100 High Street
Southgate, London, N14 6BN
WWW.U-POL.COM

UK Sales
T: +44 (0)20 8492 5920
F: +44 (0)20 8150 5605
uk.sales@u-pol.com

International
T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical
T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com