

1. PRODUCT AND COMPANY IDENTIFICATION

1.01 Product Name	Colormax Etch Primer
1.02 Manufacturer/Supplier	Ultrimax Coatings Ltd
1.03 Address	Shaw Lane Industrial Estate, Ogden Road, Doncaster, DN2 4SE
1.04 Contact	www.ultrimaxcoatings.co.uk
1.05 Phone Number	01302 856666
1.06 Fax Number	01302 571510
1.7 Emergency Phone Number	01302 856666

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

·Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS05 corrosion

Eye Dam. 1

H318 Causes serious eye damage.

GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R36:

Irritating to eyes.

F+; Extremely flammable

R12:

Extremely flammable.

N; Dangerous for the environment

R51/53:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66-67:

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

Has a narcotising effect.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.



2. HAZARDS IDENTIFICATION (cont)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

Signal word Danger

Hazard-determining components of labelling:

butan-1-ol

acetone

n-butyl acetate

propan-2-ol

Hazard statements

H222-H229

Extremely flammable aerosol. Pressurised container: May burst if heated.

H318

Causes serious eye damage.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P102

Keep out of reach of children.

P260

Do not breathe spray.

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251

Pressurized container: Do not pierce or burn, even after use.

P211

Do not spray on an open flame or other ignition source.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container in accordance with local regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Xi R36 F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	20-25%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether F+ R12 Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas C, H280	12.5-20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate R10-66-67 Flam. Liq. 3, H226 STOT SE 3, H336	12.5-20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	5-10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 9004-70-0	Nitrocellulose (nitrogen content <12.6%) F R11 Flam. Sol. 1, H228	2.5-5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol Xn R22 Xi R37/38-41 R10-67 Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40-xxxx	trizinc bis(orthophosphate) N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Xi R36 F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1-2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-2.5%

4. FIRST AID MEASURES SYMPTONS

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Generally the product does not irritate the skin.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. Firefighting measures

Extinguishing media Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7. HANDLING & STORAGE

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

8. Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1,3-diene)

71-36-3 butan-1-ol

WEL S Short-term value: 154 mg/m³, 50 ppm

Sk

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

Additional information:

The lists valid during the making were used as basis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION (cont)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

Respiratory protection:

Not required.

Protection of hands:

Not required.

Material of gloves

Not required.

Penetration time of glove material

Not required.

Eye protection:



Tightly sealed goggles

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance:

Form: Aerosol
Colour: According to product
specification
Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.
Flash point: < 0 °C (< 32 °F)
Not applicable, as aerosol.

Flammability (solid, gaseous):

Not applicable.

Ignition temperature:

240 °C (464 °F)

Decomposition temperature:

Not determined.

Self-igniting:

Product is not selfigniting.

Danger of explosion:

Product is not explosive.

However, formation of
explosive air/vapour
mixtures are possible.

Explosion limits:

Lower: 1.2 Vol %

Upper: 26.2 Vol %

9.2 Other information

No further relevant information available.

Vapour pressure at 20 °C (68 °F): 4000 hPa (3000 mm Hg)
Density at 20 °C (68 °F): 0.819 g/cm (6.835 lbs/gal)
Relative density: Not determined.
Vapour density: Not determined.
Evaporation rate: Not applicable.
Solubility in / Miscibility with water:
Not miscible or difficult to mix.
Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.

Solvent content:

Organic solvents: 81.4 %
EU-VOC: 666.4 g/l
EU-VOC in %: 81.36 %
Solids content: 1 3.0 %

10. STABILITY & REACTIVITY

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions:

No dangerous reactions known.

Conditions to avoid:

No further relevant information available.

Incompatible materials:

No further relevant information available.

Hazardous decomposition products:

No dangerous decomposition products known.

11. TOXICOLOGICAL INFORMATION

LD/LC50 values relevant for classification:
67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	39 mg/m3 (rat)

115-10-6 dimethyl ether

Inhalative	LC50 / 4 h	308 mg/m3 (rat)
------------	------------	-----------------

123-86-4 n-butyl acetate

Oral	LD50	10770 mg/kg (rat)
Dermal (rabbit)	LD50	>17600 mg/kg
Inhalative	LC50 / 4 h	>21.0 mg/m3 (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	35.7 mg/m3 (rat)

106-97-8 butane

Inhalative	LC50 / 4 h	658000 mg/m3 (rat)
------------	------------	--------------------

71-36-3 butan-1-ol

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17.76 mg/m3 (rat)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	522 mg/kg (mouse)
		>5000 mg/kg (rat)

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50 / 4 h	30 mg/m3 (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	22.1 mg/m3 (rat)

Primary irritant effect:

on the skin:	No irritant effect.
on the eye:	Irritating effect.
Sensitisation:	No sensitising effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12. ECOLOGICAL INFORMATION

Aquatic toxicity:

67-64-1 acetone

EC50 / 48 h 8800 mg/l (daphnia magna)

LC50 / 48 h 2262 mg/l (daphnia magna)

LC50 / 96 h (static) 5540 mg/l (fish)

115-10-6 dimethyl ether

EC50 / 48 h >4000 mg/l (daphnia magna)

123-86-4 n-butyl acetate

EC50 / 48 h 44 mg/l (daphnia magna)

EC50 / 96 h 320 mg/l (algae)

LC50 / 24 h 205 mg/l (daphnia magna)

LC50 / 96 h 18 mg/l (Pimephales promelas)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 408 mg/l (daphnia magna)

71-36-3 butan-1-ol

EC50 / 48 h 1328 mg/l (daphnia magna)

EC50 / 72 h 8500 mg/l (algae)

LC50 / 96 h 1376 mg/l (Pimephales promelas)

7779-90-0 trizinc bis(orthophosphate)

EC50 / 48 h 0.04 mg/l (daphnia magna)

EC50 / 72 h 0.136 mg/l (algae)

LC50 / 96 h 0.14 mg/l (fish)

67-63-0 propan-2-ol

EC50 / 48 h 13299 mg/l (daphnia magna)

LC50 / 96 h (dynamic) 4200 mg/l (fish)

1330-20-7 xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h 13.5 mg/l (fish)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*

15 01 04

waste paint and varnish containing organic solvents or other dangerous substances
metallic packaging

Uncleaned packaging:

Recommendation: Non contaminated packagings may be recycled.

14. TRANSPORT INFORMATION

14.1 UN-Number

· ADR, IMDG, IATA UN 1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS

IMDG AEROSOLS

IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR

Class 2 5F Gases.

Label 2.1

IMDG, IATA

Class 2.1

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Gases.

Danger code (Kemler): -

EMS Number: F-D,S-U

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport category 2

Tunnel restriction code D

IMDG

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

UN "Model Regulation":

UN1950, AEROSOLS, 2.1

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Department issuing MSDS: R&D legislation and regulatory advisor

· Contact: QHSE Department

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Sol. 1: Flammable solids, Hazard Category 1

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· * Data compared to the previous version altered.