

COLORMAX[®]

High Build Primer - Beige, Grey & White

High Build Primer is a primer-surfacer combining ultra high filling properties with very quick drying times. Resulting in an easily sanded non-porous surface that is suitable for any topcoat.

- Super high build primer filler
- Fast drying
- Excellent smooth finish
- Very easily sanded

SUITABLE SUBSTRATES

Correctly prepared bare steel

APPLICATION DATA



2-3 coats @ 30 - 60µm



12 - 15 minutes @ 20°C



5-100 Minutes



Coloured Topcoat

APPLICATION METHOD



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.

TECHNICAL DATA

Chemical base	Acrylic Resin
VOC content	271 g/500ml
Coverage	1.6 - 2.2m ²
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

Environmentally sound: The products supplied by Ultrimax are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal: Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

