



## Colormax Zinc Galvanising Spray

- Excellent corrosion prevention
- Heat-resistant up to 250°C
- Fast drying with good spraying properties and good coverage
- Excellent adhesion and is spot weld able
- Resistant to petrol, chemicals and external elements

### SURFACE PREPARATION

The surface must be free from all contamination including rust, grease and moisture.

Before use, carefully read and note the warning text on the label

Before application, ensure that the mixing balls in the aerosol are moving freely as this ensures that the zinc content is being physically mixed into the paint.

### APPLICATION DATA



1.56 - 2.19m<sup>2</sup>  
per 500ml



Dust Free 15 minutes  
Touch Dry 20 - 30 minutes  
Overcoatable after 24 hours  
The drying time depends on temperature, air humidity and thickness of the applied coat.

- Excellent corrosion prevention
- High coverage
- Fast drying
- Petrol and chemical resistant

### APPLICATION METHOD



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.

### TECHNICAL DATA

Product Type Epoxyester

**Environmentally sound:** The products supplied by Ultrimax are 100% free of heavy metals and the caps and packaging are made of recyclable material.

**Disposal:** Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

