



## Primer Grey, Red or White

- Excellent corrosion prevention
- Optimizes the gloss finish of the topcoat
- Fast drying with good spraying properties and good coverage
- Excellent adhesion of subsequent topcoat
- Excellent filling properties and easy to sand
- Will adhere to wood, metal, aluminium and many other substrates

### APPLICATION DATA

Product Type Nitro Combi



1.56 - 2.19m<sup>2</sup> per 500ml



Dust Free 5 - 10minutes  
Touch Dry 10 - 20 minutes  
Overcoat after 2 hours

The drying time depends on temperature, humidity and the thickness of the applied coat.



Sand able after 2 hours

### APPLICATION METHOD



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.

### SURFACE PREPARATION

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

