

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

#### 1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: ProXL® PLASTIC CLEANER 500 ML
- · Article number: PROCLEANER
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ProXL

Second Avenue

Chatham

Kent

ME4 5AU

Tel: +44 (0)1634 823900 Fax: +44 (0)1634 823909 Email: info@pro-xl.co.uk

- · Further information obtainable from: QHSE Department
- · 1.4 Emergency telephone number:

Tel: +44(0) 1634 823900 (08.00 / 17.00)

(24 h/d, 7 d/wk)

#### 2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Acute Tox. 4

H332

Harmful if inhaled.

STOT SE 3

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3 H412

Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R37.

Irritating to respiratory system.



F+; Extremely flammable

R12:

Extremely flammable.

R52/53-66-67:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

(Contd. of page 1)

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

Has a narcotizing effect.

#### · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02



### · **Signal word** Danger

#### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2) Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

*P211* Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents/container in accordance with local regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

#### 3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

| CAS: 64742-48-9                | Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS  | d. of page 50-75% |
|--------------------------------|--|-------------------|
| EINECS: 265-150-3              | nr. 71-43-2)   | 30 737            |
| Index number: 649-327-00-6     | <b>★</b> Xn R65  |                   |
| Reg.nr.: 01-2119463258-33-xxxx | R10-66-67  |                   |
|                                | ♠ Flam. Liq. 3, H226   |                   |
|                                | <b>♦</b> Asp. Tox. 1, H304                                   |                   |
|                                | ₹ STOT SE 3, H336  |                   |
| CAS: 64742-95-6                | Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS | 20-259            |
| EINECS: 265-199-0              | nr. 71-43-2)   |                   |
| Index number: 649-356-00-4     | <b>★</b> Xn R65  |                   |
| Reg.nr.: 01-2119455851-35-xxxx | <b>▼</b> Xi R37  |                   |
|                                | N R51/53   |                   |
|                                | $\overline{RI}0$ -66-67                                      |                   |
|                                | Carc. Cat. 2, Muta. Cat. 2                                   |                   |
|                                | ♠ Flam. Liq. 3, H226   |                   |
|                                | <i>♦ Asp. Tox. 1, H304</i>                                   |                   |
|                                | Aquatic Chronic 2, H411                                      |                   |
|                                | ♦ STOT SE 3, H335-H336                                       |                   |
| CAS: 74-98-6                   | <u>propane</u>   | 5-10%             |
| EINECS: 200-827-9              | <b>▶</b> F+ R12  |                   |
| Index number: 601-003-00-5     | ♠ Flam. Gas 1, H220  |                   |
| Reg.nr.: 01-2119486944-21-xxxx |  |                   |
| CAS: 106-97-8                  | <u>butane</u>  | 5-10%             |
| EINECS: 203-448-7              | F+ R12   |                   |
| Index number: 601-004-00-0     | ♠ Flam. Gas 1, H220  |                   |
| Reg.nr.: 01-2119474691-32-xxxx | Press. Gas, H280   |                   |
| CAS: 75-28-5                   | <u>iso</u> butane  | 2.5-59            |
| EINECS: 200-857-2              | F+R12  |                   |
| Index number: 601-004-00-0     | ♠ Flam. Gas 1, H220  |                   |
| Reg.nr.: 01-2119485395-27-xxxx | Press. Gas, H280   |                   |

#### 4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

(Contd. of page 3)

#### 6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands: Not required.

(Contd. on page 5)

Version number 3 Revision: 13.05.2014 Printing date 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

Material of gloves Not required.
Penetration time of glove material Not required.
Eye protection: Not required.

(Contd. of page 4)

| 9.1 Information on basic physical an<br>General Information                         | a cnemical properties   |
|---|---|
| Appearance:<br>Form:<br>Colour:<br>Odour:<br>Odour threshold:                       | Aerosol<br>Colourless<br>Characteristic<br>Not determined.                                  |
| oH-value:   | Not determined.   |
| Change in condition<br>Melting point/Melting range:<br>Boiling point/Boiling range: | Undetermined.<br>Not applicable, as aerosol.  |
| Flash point:  | < 0 °C (< 32 °F)<br>Not applicable, as aerosol.   |
| Flammability (solid, gaseous):  | Not applicable.   |
| gnition temperature:  | 240 °C (464 °F)   |
| Decomposition temperature:  | Not determined.   |
| Self-igniting:  | Product is not selfigniting.  |
| Danger of explosion:  | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits:<br>Lower:<br>Upper:   | 0.6 Vol %<br>7.0 Vol %  |
| Vapour pressure at 20 °C (68 °F):   | 3500 hPa (2625 mm Hg)   |
| Density at 20°C (68°F):<br>Relative density<br>Vapour density<br>Evaporation rate   | 0.755 g/cm³ (6.3 lbs/gal) Not determined. Not determined. Not applicable.                   |
| Solubility in / Miscibility with water:   | Not miscible or difficult to mix.   |
| Partition coefficient (n-octanol/water  | r): Not determined.   |
| /iscosity:<br>Dynamic:<br>Kinematic:  | Not determined.<br>Not determined.  |
| Solvent content: Organic solvents: EU-VOC: EU-VOC in %:                             | 100.0 %<br>755.0 g/l<br>100.00 %  |

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

(Contd. of page 5)

### 10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

| Acute toxi | cuy.         |  |
|------------|--------------|--|
| · LD/LC50  | values relev | ant for classification:  |
| 64742-48-  | 9 Naphtha (  | petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)  |
| Oral       | LD50         | >15000 mg/kg (rat)   |
| Dermal     | LD50         | >3000 mg/kg (rab)  |
| Inhalative | LC50 / 4 h   | >2.8 mg/m3 (rat)   |
| 64742-95-  | 6 Solvent na | uphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2) |
| Oral       | LD50         | 3592 mg/kg (rat) (OECD401)                                       |
| Dermal     | LD50         | >3160 mg/kg (rab) (OECD402)                                      |
| Inhalative | LC50 / 4 h   | >6193 mg/m3 (rat)  |
| 106-97-8 b | utane        |  |
| Inhalative | LC50 / 4 h   | 658000 mg/m3 (rat)   |

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

### 12 Ecological information

· 12.1 Toxicity

| 4    | . •     |           |  |
|------|---------|-----------|--|
| 40   | nintic. | toxicity: |  |
| 71 U | nuite   | wallu.    |  |

64742-48-9 Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)

LC50 / 96 h > 100 mg/l (fish)

64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)

EC50 / 24 h | 150 mg/l (daphnia magna)

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h | 3.77 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 7)

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European | waste catalogue    |
|------------|--------------------|
| 20 01 13*  | solvents           |
| 15 01 04   | metallic packaging |

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

| 14.1 UN-Number<br>ADR, IMDG, IATA                | UN1950              |    |
|--|---------------------|----|
| 14.2 UN proper shipping name                     | 2.11200             |    |
| ADR  | 1950 AEROSOLS       |    |
| <i>IMDG</i>                                      | AEROSOLS            |    |
| IATA   | AEROSOLS, flammable |    |
| 14.3 Transport hazard class(es)                  |                     |    |
| ADR  |                     |    |
|  |                     |    |
|  |                     |    |
|  |                     |    |
|  |                     |    |
| Class  | 2 5F Gases.         |    |
| Label  | 2.1                 |    |
| IMDG, IATA                                       |                     |    |
|  |                     |    |
|  |                     |    |
|  |                     |    |
| Class  | 2.1                 |    |
| Label  | 2.1                 |    |
|  |                     | N. |
| 14.4 Packing group<br>ADR, IMDG, IATA            | Void                |    |
|  |                     |    |
| 14.5 Environmental hazards:<br>Marine pollutant: | No                  |    |
| 14.6 Special precautions for user                | 110                 |    |

onta. on page o

Printing date 13.05.2014 Version number 3 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

|  | (Contd. of p          | age |
|--|-----------------------|-----|
| · Danger code (Kemler):                    | -                     |     |
| EMS Number:                                | F- $D$ , $S$ - $U$    |     |
| · 14.7 Transport in bulk according to Anno | ex II of              |     |
| MARPOL73/78 and the IBC Code               | Not applicable.       |     |
| · Transport/Additional information:        |                       |     |
| · ADR                                      |                       |     |
| · Limited quantities (LQ)                  | IL                    |     |
| Transport category                         | 2                     |     |
| · Tunnel restriction code                  | D                     |     |
| · UN "Model Regulation":                   | UN1950, AEROSOLS, 2.1 |     |

### 15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R12 Extremely flammable.
- R37 Irritating to respiratory system.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: QHSE Department
- · Contact: QHSE Department
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

(Contd. on page 9)

Version number 3 Printing date 13.05.2014 Revision: 13.05.2014

Trade name: ProXL® PLASTIC CLEANER 500 ML

(Contd. of page 8)

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 · \* Data compared to the previous version altered.

