

1. PRODUCT AND COMPANY IDENTIFICATION

1.01 Product Code	Ultrithane
1.02 Manufacturer/Supplier	Ultrimax Coatings Ltd
1.03 Address	Shaw Lane Industrial Estate, Ogden Road, Doncaster, DN2 4SE
1.04 Contact	www.ultrimaxcoatings.co.uk
1.05 Phone Number	01302 856666
1.06 Fax Number	01302 571510
1.7 Emergency Phone Number	01302 856666

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture: Mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

GHS02

GHS08

GHS09

Signal word Danger

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; d~ Aquatic Chronic 2, H411; STOT SE 3, H336	25-50%
EC number: 918-668-5 Reg.nr.: 01-211945851-35-xxxx	Solvent naphtha (petroleum), light aromatic Flam. Liq. 3, H226; d~ Asp. Tox. 1, H304; d~ Aquatic Chronic 2, H411; STOT SE 3, H335-H336	2.5-10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; d~ Asp. Tox. 1, H304; STOT SE 3, H336	2.5-10%
EC number: 927-344-2	Hydrocarbons, C9 - C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; d~ Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H336	≤ 2.5%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	≤ 2.5%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	≤ 2.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 1B, H360F; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≤ 2.5%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General information:	Immediately remove any clothing soiled by the product.
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.
After eye contact:	Rinse opened eye for several minutes under running water.
After swallowing:	Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Mount respiratory protective device.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7. HANDLING & STORAGE

7.1 Precautions for safe handling

Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
Hygiene measures:
Wash hands before breaks and at the end of workday.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.

7.3 Specific end use(s)

No further relevant information available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Solvent naphtha (petroleum), light aromatic

OEL Long-term value: 100 mg/m³

Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

OEL Short-term value: 1200 mg/m³

96-29-7 2-butanone oxime

OEL Long-term value: 1 mg/m³, 0.3 ppm

136-52-7 cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

DNELs

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral DNEL 26 mg/day (Con)

Dermal DNEL 26 mg/day (Con)

44 mg/day (Ind)

Inhalative DNEL 71 mg/m³ (Con)

330 mg/m³ (Ind)

Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral DNEL 125 mg/day (Con)

Dermal DNEL 125 mg/day (Con)

208 mg/day (Ind)

Inhalative DNEL 185 mg/m³ (Con)

871 mg/m³ (Ind)

Solvent naphtha (petroleum), light aromatic

Oral DNEL 11 mg/day (Con)

Dermal DNEL 11 mg/day (Con)

25 mg/day (Ind)

Inhalative DNEL 32 mg/m³ (Con)

150 mg/m³ (Ind)

96-29-7 2-butanone oxime

Dermal DNEL 0.78 mg/day (Con)

1.3 mg/day (Ind)

Inhalative DNEL 2.7 mg/m³ (Con)

9 mg/m³ (Ind)

Additional information: The lists valid during the making were used as basis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.

Respiratory protection:

When spraying the product, use a respiratory protective device.

Protection of hands:

Protective gloves

Eye protection:

Tightly sealed goggles



9. PHYSICAL & CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid
Colour: Clear
Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 135 °C
Flash point: >30 °C
Flammability (solid, gas): Not applicable.
Ignition temperature: >200 °C
Decomposition temperature: Not determined.
Auto-ignition temperature: Product is not self-igniting.
Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:
Lower: 0.6 Vol %
Upper: 7.0 Vol %
Vapour pressure: Not determined.
Density at 20 °C: 0.914 g/cm³
Relative density: Not determined.
Vapour density: Not determined.
Evaporation rate: Not determined.
Solubility in / Miscibility with water: NOT MISCIBLE
Partition coefficient: n-octanol/water: Not determined.
Viscosity:
Dynamic at 20 °C: 230 mPas
Kinematic: Not determined.
Solvent content:
Organic solvents: 42.1 %
Solids content: 50.8 %

9.2 Other information No further relevant information available.

10. STABILITY & REACTIVITY

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral LD50 >15,000 mg/kg (Rat)

Dermal LD50 >3,400 mg/kg (Rab)

Inhalative LC50/4 h 13.1 mg/l (Rat)

Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral LD50 >5,000 mg/kg (Rat)

Dermal LD50 >5,000 mg/kg (Rat)

Solvent naphtha (petroleum), light aromatic

Oral LD50 3,492 mg/kg (rat)

Dermal LD50 3,160 mg/kg (Rab)

Inhalative LC50/4 h >6.193 mg/l (rat)

96-29-7 2-butanone oxime

Oral LD50 2,326 mg/kg (rat)

Dermal LD50 1,000 mg/kg (Rab)

200-2,000 mg/kg (rat)

Inhalative LC50/4 h >4.8 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity:

Acute Fish toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

LC50 9.22 mg/l

Species: Oncorhynchus mykiss (rainbow trout)

Exposure duration: 96 h

Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 6.14 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 48 h

Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

ErC50 2.9 mg/l

Species: Pseudokirchneriella subcapitata (green algae)

Exposure duration: 72 h

Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

14.1 UN-Number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG PAINT (Solvent naphtha (petroleum), light aromatic),
MARINE POLLUTANT
IATA PAINT

14.3 Transport hazard class(es)

ADR, IMDG

Class 3 Flammable liquids.
Label 3



IATA 3 Flammable liquids.
Class 3
Label 3



14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: Product contains environmentally hazardous substances: cobalt bis(2-ethylhexanoate)
Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user

Warning: Flammable liquids.
Hazard identification number (Kemler code): 30
EMS Number: F-E,S-E
Stowage Category A

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information:

ADR Not applicable.
Limited quantities (LQ) 5L
Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
Transport category 3
Tunnel restriction code D/E
IMDG
Limited quantities (LQ) 5L
Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation": UN 126 3 PAINT, 3, I I I , ENVIRONMENTALLY HAZARDOUS

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Technical instructions (air):

Class	Share in %
I	0.3
NK	42.1

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Full text of H-Statements referred to under sections 2 and 3:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H360F May damage fertility.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Product safety department: LABORATORY

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - oral – Category 4
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for his own particular use.