

TABLE OF THINNERS

TYPE	GENERAL CHARACTERISTICS
DE 703	For general use with air-drying coatings.
DP 695	For general use with polyester coatings. Free of aromatic solvents.
DP 705	Reactive Thinner for polyester coatings to be used in a max quantity of 5% when a higher flow is required such as during summer or in tropical areas, it prevents pin holes during application of the polyester Basecoat.
DS 1105	General use for nitrocellulose coatings.
DT 4	Extremely quick Thinner for polyurethane coatings. It extends the pot-life significantly. Free of aromatic solvents.
DT 13	Very quick Thinner, with good wettability, free of aromatic solvents.
DT 40	Average Thinner, free of aromatic solvents, extremely wetting.
DT 90	Average polyurethane Thinner. It facilitates the floating and levelling of the matting agent.
DT 424	Slow Thinner specific for glossy products. Free of aromatic solvents.
DT 441	Retardant Additive particularly useful for the application by spray of gloss lacquered products in summer months.
DT 1146	Retardant Thinner for polyurethane coatings, suitable for summer months.
DT 1150	General use for polyurethane coatings.
DX 983	Thinner for Paints applied by spray and roller. It is a retardant and improves substrate wetting.
DX 986	Wetting Thinner for solvent-based Stains. Free of aromatic solvents.
DX 1131	Thinner for solvent-based Stains and Glazes and polyesters. It dries very quickly. It is suitable for polyester products. Free of aromatic solvents.