# 1K Ultra Clear Lacquer



Clear Lacquer Pro is a high performance 1K lacquer which gives a crystal clear finish that can be applied over all water and solvent based basecoats and is ideal for smart repairs.

- Ultra gloss finish with excellent gloss retention
- Superior build
- UV and petrol resistant
- Fast drying

#### **SUITABLE SUBSTRATES**

Solvent based basecoat paints

#### **APPLICATION DATA**



2-3 coats @ 50µm



Dust dry Touch dry Re-Coat 5 -10 minutes @ 20°C 10-20 minutes @ 20°C 2 minutes @ 20°C

The drying time depends on temperature, air humidity and thickness of the applied coat.



15-20 Minutes



UV 20°C 40°C 15-20 minutes 24 hours 40 minutes

### APPLICATION METHOD



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.

## **TECHNICAL DATA**

Chemical base

Acrylic Resin

Gloss level

85-90 (60° to DIN 67530)

Temp resistance VOC content

345g/500ml

110°C

Coverage

1.9 - 2.5m<sup>2</sup>

Storage notes

10 years in appropriate storage

(-10°-25°C, relative air humidity of max. 60%)

**Environmentally sound:** The products supplied by Ul; trimax are 100% free of heavy metals and the caps and packaging are made of recyclable material.

**Disposal:** Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

